

1 MP Indoor Network Cube Camera

DIS-9401IP-E



Feature

- 1.0 Megapixel High Sensitivity CMOS Sensor
- 720p HD Images up to 30 fps
- H.264/MPEG-4/MJPEG Video Compression
- Power Over Ethernet (PoE) 802.3af
- Compatible with CMS software

Specification

Model	DIS-9401IP-E
Sensor Imager	1/4" CMOS Imager 1280 x 720 (720p) 1 Mpx
Minimum Illumination	1.0 Lux
Lens	3.6 mm Fixed Lens
Angle of View	60°(H) x 45°(V)
IR-Cut Filter	Yes
Video Compression	H.264/M-JPEG/MPEG-4 Tri-Encoders works simultaneously
Resolution	1280x720(720p), 640x480(VGA), 320x240 (QVGA), 160x120(QQVGA)
Encoding Rate	Up to 30fps @ 1280 x 720
Audio Compression	AAC, AMR
Audio Stream	Two-way
Audio Input/Output	Built-in MIC input
Simultaneous Viewers	16
Ethernet	RJ45 (10/100Base-T)
Protocol	HTTP, TCP/IP, ICMP, DHCP, RTSP, RTP, RTCP, UPnP, 3GPP, SMTP, NTP, DHCP, DNS, NAS, PPPoE, DDNS, FTP
Record Mode	Motion Alarm, Contact Alarm, Time Schedules and Snapshot
Operating System	Windows 2000/XP/Vista/Win7, Mac, Linux, iPhone, iPad, Android
Processor	Intel Pentium III, 1 GHz or higher
Memory	256 MB Minimum
Internet Browser	Microsoft IE ver.5.5 or higher, Safari, Mozilla, Firefox, Google Chrome etc.
Power Supply	PoE 802.3af
Power Consumption	3.75W
Operating Temperature	-5°C ~ 45°C, Humidity: 20% ~ 90% (Non-condensing)
Dimension	85 x 85 x 39 mm
Weight	160 g